



Scale : 1/2

- NOT : 1-This rim has all specifications of E.T.R.T.O.)
 2-This rim welding has all specifications of DIN 1912.
 3-(Primer is cataferitic system. (Grey) Top coating is RAL 9006.)
 4-(Rim, has not sharp corner.
 5- (Thickness is 50±10 Micron.)
 6- (Max. disbalance 2000 g*cm.)
 7. (Salt test resistance time min. 504 hours.)
 8-(Wheel load capacity 7500kg for 20km/h and 5000kg for 100 km/h.)

WHEEL WEIGHT: 42,5 kg ± 0.5

30	1	3	(VALVE)	V3.22.1	
31	1	2	(DISC)	1122014.35	S 275 JRC (E 3944)
	1	1	(RIM)	112260001	S 275 JRC (E 3944) 6 ± 0,2
	ADET	PRÇ. NO (PART NO)	(PART NAME)	(DRAWING NO)	AÇIKLAMA (DESCRIPTION)
	(DRAWING BY)	(DATE)	(NAME)	(SIGNATURE)	MEGA TORK
	(CHECKED BY)	14.04.2021	F.VURAL		
	(APPROVED BY)	14.04.2021	Ö.ABREKOĞLU		
	SCALE	1/1 (1/2)			(DRAWING NO)
		11,75 x 22,5 WHEEL (120 OFFSET)			1122614.35,0
					MEGA TORK

Revisior No	(NAME CHANGE)	(DATE)	(APPROVED BY)
-------------	---------------	--------	---------------